

Alpha Digital Services Ltd
111 Loverock Road,
Reading RG30 1DZ

Tel: 01189 337000
Fax: 01189 587950



www.alphadigitalservices.co.uk

RICOH Caplio GX100

DIGITAL CAMERA



- 24-72mm optical zoom lens.
- 10 megapixel CCD.
- 19mm wide angle conversion lens available.
- Removable electronic viewfinder.
- 7 blade iris aperture.
- Vibration correction and high sensitivity.
- 1cm macro.
- Versatile exposure modes.
- Flexible shooting functions.
- Wide range of accessories available.
- RAW file format.

CCD	Effective 10.01 million pixels (total 10.30 million pixels), 1/1.75-inch primary-color CCD
LENS	Focal length: f=5.1 - 15.3 mm (35mm camera equivalent, 24-72mm) Aperture (F value): F2.5(Wide) - F4.4(Tele) Lens construction: 11 elements in 7 groups
VIBRATION CORRECTION FUNCTION	CCD shift method
DIGITAL ZOOM	Optical: 3X (35mm camera equivalent, 24-72mm) Digital: 4X (Maximum 12X when combined with optical)
SHOOTING DISTANCE	Approx. 30 cm - infinity from lens tip (Wide and Tele)
MACRO SHOOTING	APPROX. 1 CM - INFINITY FROM LENS TIP (WIDE), APPROX. 4 CM - INFINITY FROM LENS TIP (TELE) APPROX. 1 CM - INFINITY FROM LENS TIP (ZOOM MACRO MODE)
SHUTTER SPEED	STILL IMAGE: 180, 120, 60, 30, 15, 8, 4, 2, 1-1/2000 SEC. Movie: 1/30 - 1/2000 sec.
PIXELS	Still image: 3648 x 2736, 3648 x 2432, 2736 x 2736, 3264 x 2448, 2592 x 1944, 2048 x 1536, 1280 x 960, 640 x 480 Text: 3648 x 2736, 2048 x 1536 Movie: 640 x 480, 320 x 240
PICTURE MODE	F (Fine) / N (Normal) / RAW
ISO SENSITIVITY	AUTO, AUTO-HI, ISO80 / ISO100 / ISO200 / ISO400 / ISO800 / ISO1600
FLASH	Off, Auto, Red-eye reduction, On, Slow synchro, Soft Flash Flash range: Approx. 0.2 - 5.0 m (Wide), 0.15 - 3.0 m (Tele)
FOCUS	Auto Focus, Spot Auto Focus, Manual Focus, Snap (Fixed Focus), Infinity
EXPOSURE ADJUSTMENT	TTL-CCD Metering method (AE lock possible for all meterings.): Multi light metering (256 segments), Center-weighted light metering, Spot metering
EXPOSURE COMPENSATION	Manual exposure Compensation +2.0EV - -2.0EV (1/3EV Steps), Auto Bracket Function (-0.3EV, ±0, +0.3EV / -0.5EV, ±0, +0.5EV)
WHITE BALANCE	Auto, Fixed (Outdoors, Cloudy, Incand., Fluores., Manual) / White Balance Bracket
MEMORY TYPE	2.5-inch Transparent Amorphous Silicon TFT LCD (approx. 230,000 pixels)
LCD MONITOR DISPLAY	PC: USB2.0/Video Out
BATTERY	Rechargeable battery (DB-60) x 1, optional AC adaptor (AC-4c), AAA battery (alkaline / oxyride / NiMH) x 2
WEIGHT	Approx. 220 g (excluding batteries, Memory Card, strap), Accessories: approx. 30 g (battery, strap)
DIMENSIONS	111.6 mm (W) x 58.0 mm (H) x 25.0 mm (D) (excluding projections parts)

Ricoh Caplio GX100

SRP £349.99

Ricoh Caplio GX100 VF KIT

SRP £399.99

Please contact for list of
available accessories.

**MANUFACTURER'S
WARRANTY PERIOD
2 YEARS**

RICOH

DIGITAL CAMERAS

World famous for their 35mm camera
range, Ricoh now produce award
winning digital cameras.

Ricoh digital cameras are characterised
by sleek design, faster shutter speeds
and wide angle capability.

RICOH

BRAUN

Liesegang
projection technology

DXO

iView MediaPro
Manage your creativity

SAGEM